ProLite E2472HD-1

The ProLite E2472HD LED-backlit monitor is a full high definition 24” display that features all the benefits this technology affords. Slender and stylish its maximum width is 3cm, it has a narrow 1.7cm bezel, touch sensitive controls and is finished in the latest glossy-black. The high specifications on the monitor include the 5,000,000:1 ACR, fast 2ms response for excellent sharpness in high definition video and triple input connectivity (D-Sub, DVI-D, HDMI). With Eco-mode activated power consumption is down to typically 13W and less than 1W in standby.

Panel	LED-Backlit
Diagonal	24"
Display area h x w	298.89 x 531.36 mm; 11.8" x 20.9"
Response time	2 ms
Contrast	5 000 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.277 x 0.277 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	31 - 83 KHz
Vertical sync	56 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
HDCP	yes
Output connector	Audio out (only with HDMI input)
Synchronization	Separate sync
Plug & Play	VESA DDC2B™
Included accessories	AC adapter, power cable, D-Sub cable, DVI-D cable, stand, screw, quick start guide, safety guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 10 languages (EN, DE, FR, ES, IT, PL, NL, Chinese, RU, JP) and 6 front controls (Power, Menu/ Select, Scroll up, Scroll down/ ECO, Exit, Auto)
User controls	audio adjust, luminance (brightness, contrast), geometry (H. position, V. position, pixel clock, phase), colour, OSD (H. position, V. position, OSD time), language, recall, miscellaneous (sharpness, DDC/CI, display information, ACR, display mode, OD, opening logo), input select, audio (volume, mute)
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Ergonomics	CE,VCCI-B,TUV-Bauart
Power supply	DC 12V 3A
Power Supply Unit	external
Power usage	24 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
Tilt angle	15° up; 5° down
Dimensions w x h x d	570 x 420 x 179 mm
Weight	3.8 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.